

Product Specification Sheet

Philips SL190 9W

Philips SL190 9W 2700K

Brand: Philips
Wattage: 9W
Colour temperature: 2700K
Series: SL190
Product type: Integrated LED spotlight
Application: Indoor accent and general lighting
Mounting / form factor: Recessed ceiling installation
Manufacturer reference / 12NC: 929004131807

Philips SL190 9W 4000K

Brand: Philips
Wattage: 9W
Colour temperature: 4000K
Series: SL190
Product type: Integrated LED spotlight
Application: Indoor accent and general lighting
Mounting / form factor: Recessed ceiling installation
Manufacturer reference / 12NC: 929004131907

Philips SL190 9W 6500K

Brand: Philips
Wattage: 9W
Colour temperature: 6500K
Series: SL190
Product type: Integrated LED spotlight
Application: Indoor accent and general lighting
Mounting / form factor: Recessed ceiling installation
Manufacturer reference / 12NC: 929004640807

Compiled by StarLuma. Original manufacturer range pages follow; select the matching product reference in the table.
contact@starluma.pk | starluma.pk

THE STAR TRADERS



The Integrated LED Spotlight is a smart, all-in-one lighting solution designed for performance and simplicity. With the LED module built directly into the fixture, it eliminates the need for bulb replacements while delivering high-quality, directional seamless light.

Benefits and Features

- ✓ Built-In LED Module.
- ✓ High Lumen Output.
- ✓ Slim, Modern Housing
- ✓ Low Maintenance.

Applications

- ✓ Bed - Living Rooms
- ✓ Hallways, Staircases
- ✓ Retail stores
- ✓ Work Areas

Product Types	Voltage	Wattage	Frequency	Color Temp	Lumen Output	CRI	Lifetime	Power Factor	IP Rating	Product Code
	v	W	Hz	K	lm	01-100	hrs	-	-	Order Nr
SL052 Intergrated Spotlight	110-240V	5.8	50/60	2700	600	80	25,000	0.5	IP20	929002655461
	110-240V	5.8	50/60	6500	600	80	25,000	0.5	IP20	929002655661
SL190 High Wattage	220-240	9	50/60	2700	800	80	15,000	0.5	IP20	929004131807
	220-240	9	50/60	2700	800	80	15,000	0.5	IP20	929004131907
	220-240	9	50/60	2700	800	80	15,000	0.5	IP20	929004640807
SL052 Square Downlight	110-240	4.2	50/60	2700	350	80	15,000	0.5	IP20	929002655101
	110-240	4.2	50/60	6500	350	80	15,000	0.5	IP20	929002655301
	110-240	6.2	50/60	2700	550	80	15,000	0.5	IP20	929002655701
	110-240	6.2	50/60	6500	550	80	15,000	0.5	IP20	929002655901